



FORTY (40) YEAR WARRANTY PREPAINTED COLOURS

DOMTEK BUILDING PRODUCT'S POLICY OF QUALITY AND DURABILITY IN THE MANUFACTURE OF ITS PAINTED ROOFING AND SIDING PRODUCTS, ARE REPRESENTED BY THIS LIMITED WARRANTY, UNLESS OTHERWISE NOTED. THIS WARRANTY IS VALID FOR A PERIOD OF FORTY (40) YEARS FROM THE DATE OF SHIPMENT.

WARRANTY COVERAGE

1. During the terms of this 40-year Limited Warranty, the painted panel will not perforate or fail structurally due to deterioration from red rust.
2. The paint will not:
 - A) Crack, check or peel (lose adhesion) for forty (40) years. This does not include micro-fracturing, which may occur in proper fabrication of the building parts.
 - B) Chalk in excess of a numerical rating of 8 when measured with the standard procedure specified in D4214-98, Method D659 on sidewalls for a period of thirty (30) years.
 - C) Chalk in excess of a numerical rating of 7 when measured with the standard procedure specified in D4214-98, Method D659, on roofs for a period of thirty (30) years.
 - D) Fade or change colour by more than 5 units of color for sidewall panels in accordance with the standard procedure of D-2244-02, for a period of thirty (30) years.
 - E) Fade or change colors by more than 6 units of colour for roof panels in accordance with the standard procedure of D-2244-02, for a period of thirty (30) years.
3. On non-vertical installations, the Products will not exhibit accumulation of red rust caused by acid rain on coated surfaces, for a period of ten (10) years on G-90, fifteen (15) years on G-60 HDG steel beyond 1/2 inch from edge of panel.

LIMITATIONS ON WARRANTY

1. This warranty is extended to the original buyer only and is not transferable or assignable.
2. Abnormal atmospheric conditions to which this Warranty does not apply include, but are not limited to hail, exposure to corrosive or harmful chemicals (whether solids, liquids or gases), airborne contaminants, animal wastes, exposure to sal water spray, decaying materials, wet absorptive material, and internal contamination created by improper ventilation or improper housekeeping. The warranty does not cover damage caused by acts of God, falling objects, external forces, explosions, fire, riots, civil commotion, act of war excessive radiations or other such similar or dissimilar occurrences beyond our control.
3. This warranty does not cover damage to the product's finish caused by handling, shipping, transit, processing, storage or installation.

BUYER'S OBLIGATION

1. The Buyer shall inspect material when received from Domtek Building Products prior to installation so as to mitigate expenses involved in repairing, replacing or repainting defective sheets. The Buyer accepts responsibility upon receipt of the material in the conditions described in Paragraph 3 of Limitations on Warranty.
2. Any claim on account of a defect in the products or for any other cause whatsoever shall be deemed waived by Buyer unless written notice thereof is given to the Seller within thirty (30) days after discovery of the defect and within the applicable warranty period. Buyer must submit proof of purchase in the event of such claim. Seller shall be given reasonable opportunity to investigate all claims.

EXCLUSIVE REMEDY

If any of our products fails to perform as warranted, the Company will, at its option, repaint or replace the defective panels or refund the buyer the price paid for the material. The company's total liability is expressly limited to the purchase price of the defective material. Except as provided herein the company shall not be liable for any losses, damage or expenses, whether direct, incidental or consequential, caused by or resulting from the use of defective or non-conforming, products.

THE EXPRESS WARRANTIES AND REMEDIES STATED HEREIN ARE THE EXCLUSIVE WARRANTIES AND REMEDIES APPLICABLE TO THE PRODUCTS. ALL IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED.

Agreed Procedure for Determining Conformation with Specification

For the purpose of determining whether an exposed panel meets the standards set forth above, all chalk, dirt and other film deposits on the area of the panel to be tested for colour must be removed by washing prior to evaluation.

To wash the test area, use a pad of 28/24 mesh cheesecloth and distilled water and a mild detergent cleaner. Wet the cheesecloth thoroughly with the cleaning solution and rub it, using moderate hand pressure, over an area of the panel approximately 4" x 4". Care must be taken to avoid any scratching, burnishing or other physical alteration of the coated surfaces.

After washing, as described above, flush off the test area with distilled water and allow to dry.

Failure to keep condensation or moisture from nested materials may result in damage or wet storage stain, voiding manufacturer's guarantee.

If project requires a material/finish warranty to be issued, completely fill out information below and submit to Domtek Building Products Customer.

PROJECT NAME: _____

PROJECT ADDRESS: _____

OWNER NAME: _____

INSTALLER NAME: _____

DOMTEK BLDG PRODUCTS INVOICE: _____

DOMTEK BUILDING PRODUCTS
REP SIGNATURE: _____



DOMTEK Building Products
P.O. Box 20078
Brandon, Manitoba
R7A 6Y8
1-800-665-1027

July, 2017